



GROUP 2 SPECIFICATION


1. MAJOR COMPONENT



7709S2SE01

2. SPECIFICATIONS


1) WITH BOLT-ON CUTTING EDGE TYPE BUCKET (HL775-9S)



7759S2SE03

Description		Unit	Specification	
Operating weight		kg (lb)	24170 (53285)	
Bucket capacity	Struck	m ³ (yd ³)	4.0 (5.2)	
	Heaped		4.7 (6.1)	
Overall length	A	mm (ft-in)	9490 (29' 8")	
Overall width	B		3250 (10' 8")	
Overall height	C		3600 (11' 10")	
Ground clearance	D		480 (1' 7")	
Wheelbase	E		3500 (11' 6")	
Tread	F		2300 (7' 7")	
Dump clearance at 45°	G		3040 (9' 11")	
Dump reach (full lift)	H		1330 (4' 4")	
Width over tires	I		3000 (9' 10")	
Dump angle	J		degree (°)	48
Roll back angle (carry position)	K			48
Cycle time	Lift (with load)	sec	5.9	
	Dump (with load)		1.3	
	Lower (empty)		2.6	
Maximum travel speed		km/hr (mph)	37.1 (23.1)	
Braking distance		m (ft-in)	12 (39' 4")	
Minimum turning radius (center of outside tire)			6.095 (20' 0")	
Gradeability		degree (°)	30	
Breakout force		kg (lb)	19120 (42155)	
Travel speed	Forward	First gear	7.0 (4.4)	
		Second gear	12.3 (7.6)	
		Third gear	25.8 (16.0)	
		Fourth gear	37.1 (23.1)	
	Reverse	First gear	7.0 (4.4)	
		Second gear	12.3 (7.6)	
Third gear		25.8 (16.0)		

2) WITH TOOTH TYPE BUCKET (HL775-9S)



77592SE04

Description		Unit	Specification	
Operating weight		kg (lb)	24100 (53131)	
Bucket capacity	Struck	m ³ (yd ³)	3.8 (4.97)	
	Heaped		4.5 (5.89)	
Overall length	A	mm (ft-in)	9190 (30' 2")	
Overall width	B		3300 (10' 10")	
Overall height	C		3590 (11' 9")	
Ground clearance	D		480 (1' 7")	
Wheelbase	E		3500 (11' 6")	
Tread	F		2300 (7' 7")	
Dump clearance at 45°	G		2915 (9' 7")	
Dump reach (full lift)	H		1415 (4' 8")	
Width over tires	I		3000 (9' 10")	
Dump angle	J		degree (°)	48
Roll back angle (carry position)	K			48
Cycle time	Lift (with load)	sec	5.9	
	Dump (with load)		1.3	
	Lower (empty)		2.6	
Maximum travel speed		km/hr (mph)	37.1 (23.1)	
Braking distance		m (ft-in)	12 (39' 4")	
Minimum turning radius (center of outside tire)			6.095 (20' 0")	
Gradeability		degree (°)	30	
Breakout force		kg (lb)	20200 (44533)	
Travel speed	Forward	First gear	7.0 (4.4)	
		Second gear	12.3 (7.6)	
		Third gear	25.8 (16.0)	
		Fourth gear	37.1 (23.1)	
	Reverse	First gear	7.0 (4.4)	
		Second gear	12.3 (7.6)	
Third gear		25.8 (16.0)		

3. WEIGHT

Item	kg	lb
Front frame assembly	2199	4850
Rear frame assembly	2518	5550
Front fender (LH & RH)	65	143
Counterweight	1802	3970
Cab assembly	1050	2315
Engine assembly	984	2170
Transmission assembly	760	1675
Drive shaft (front)	42	92
Drive shaft (center)	37	82
Drive shaft (rear)	21	46
Front axle (include differential)	1200	2650
Rear axle (include differential)	1280	2820
Tire (26.5-25 20PR, L3)	394	870
Hydraulic tank assembly	308	679
Fuel tank assembly	270	595
Main pump assembly	52	115
Fan & brake pump assembly	12	26
Main control valve (2 spool/3 spool)	95/115	209/254
Flow amplifier	36	79
Boom assembly	1625	3580
Bell crank assembly	460	1010
Bucket link	81	179
4.7 m ³ bucket, with bolt on cutting edge	2340	5160
4.5 m ³ bucket, with tooth	2270	5000
Boom cylinder assembly	190	419
Bucket cylinder assembly	226	498
Steering cylinder assembly	42	93
Seat	40	88
Battery	55	121

4. SPECIFICATION FOR MAJOR COMPONENTS

1) ENGINE

Item	Specification
Model	Cummins QSM11
Type	4-cycle turbocharged, charge air cooled diesel engine
Control type	Electronic control
Cooling method	Water cooling
Number of cylinders and arrangement	6 cylinders, in-line
Firing order	1-5-3-6-2-4
Combustion chamber type	Direct injection type
Cylinder bore × stroke	125 × 147 mm(4.92" × 5.79")
Piston displacement	10800cc (659 cu in)
Compression ratio	16.3 : 1
Rated gross horse power	304 ps at 2000 rpm
Maximum gross torque at 1400rpm	161 kgf · m (1165 lbf · ft)
Engine oil quantity	38 ℓ (10.0 U.S. gal)
Wet weight	984 kg (2170 lb)
High idling speed	2130 ± 50 rpm
Low idling speed	800 ± 25 rpm
Rated fuel consumption	160 g/ps · hr
Starting motor	Delco Remy 39MT(24 V)
Alternator	Delco Remy 24SI (24 V - 70 Amp)
Battery	2 × 12 V × 200 Ah

2) MAIN PUMP

Item	Specification	
	Steering	Loader
Type	Gear pump	
Capacity	134 cc/rev	72.6 cc/rev
Maximum operating pressure	210 kgf/cm ² (2990 psi)	210 kgf/cm ² (2990 psi)
Rated oil quantity	256.9 l /min (67.9 U.S.gpm)	139.2 l /min (36.8 U.S.gpm)
Rated speed	2130 rpm	

3) FAN + BRAKE PUMP

Item	Specification
Type	Variable piston pump
Capacity	28 cc/rev
Maximum operating pressure	250 kgf/cm ² (3556 psi)
Rated speed	2130 rpm

4) MAIN CONTROL VALVE

Item	Specification
Type	2 spool
Operating method	Hydraulic pilot assist
Main relief valve pressure	210 kgf/cm ²
Overload relief valve pressure	240 kgf/cm ²
Overload relief valve pressure (dump)	240 kgf/cm ²

5) REMOTE CONTROL VALVE

Item	Specification	
Type	Pressure reducing type	
Operating pressure	Minimum	5 kgf/cm ² (71 psi)
	Maximum	30 kgf/cm ² (427 psi)
Single operation angle	degree	17

6) CYLINDER

Item		Specification
Boom cylinder	Bore dia × Rod dia × Stroke	ø 180 × ø 100 × 765 mm
Bucket cylinder	Bore dia × Rod dia × Stroke	ø 200 × ø 100 × 570 mm
Steering cylinder	Bore dia × Rod dia × Stroke	ø 100 × ø 50 × 480 mm

7) DYNAMIC POWER TRANSMISSION DEVICES

Item		Specification	
Transmission	Model	ZF 4WG260	
	Type	Converter	Single-stage, single-phase
		Transmission	Full-automatic power shift
	Converter stall ratio	3.089 : 1	
	Gear shift	Forward fourth gear, reverse third gear	
	Control	Electrical single lever type, kick-down system Automatic kick down from 2nd to 1st gear	
	Pump rated flow	104 ℓ /min (27.5 U.S.gpm) at 2000 rpm	
Axle	Drive devices	4-wheel drive	
	Front	Front fixed location	
	Rear	Oscillation ± 11° of center pin-loaded	
Wheels	Tires	26.5-25, 20PR (L3)	
Brakes	Travel	Four-wheel, wet-disc type, full hydraulic	
	Parking	Spring applied, hydraulic released brake	
Steering	Type	Full hydraulic, articulated	
	Steering angle	40° to both right and left angle, respectively	

5. TIGHTENING TORQUE OF MAJOR COMPONENT

No.	Descriptions	Bolt size	Torque		
			kgf · m	lbf · ft	
1	Engine	Engine mounting bolt, nut (rubber, 2EA)	M24 × 3.0	100 ± 15	723 ± 108
2		Engine mounting bolt (bracket, 6EA)	M10 × 1.5	6.9	49.9
3		Engine mounting bolt (flywheel housing, 12EA)	3/8-16UNC	5.6 ± 1.0	40.5 ± 7.2
4		Radiator mounting bolt	M16 × 2.0	29.7 ± 4.5	215 ± 32.5
5		Fuel tank mounting bolt, nut	M16 × 2.0	29.7 ± 4.5	215 ± 32.5
6	Hydraulic system	Main pump housing mounting bolt	M16 × 2.0	29.7 ± 4.5	215 ± 32.5
7		Fan & brake pump housing mounting bolt	M10 × 1.5	6.9 ± 1.4	50 ± 10.1
8		Main control valve mounting bolt	M12 × 1.75	12.8 ± 3.0	92.6 ± 21.7
9		Steering unit mounting bolt	M10 × 1.5	6.9 ± 1.4	50 ± 10.1
10		Flow amplifier mounting bolt	M10 × 1.5	6.9 ± 1.4	50 ± 10.1
11		Brake valve mounting bolt	M8 × 1.25	2.5 ± 0.5	18.1 ± 3.6
12		Cut-off valve mounting bolt	M12 × 1.75	12.8 ± 3.0	89 ± 21.7
13		Remote control lever mounting bolt	M6 × 1.0	1.1 ± 0.2	8.0 ± 1.4
14		Safety valve	M8 × 1.25	2.5 ± 0.5	18.1 ± 3.6
15		Hydraulic oil tank mounting bolt	M20 × 2.5	57.9	419
16	Power train system	Transmission bolt, nut (rubber, 4EA)	M24 × 3.0	100 ± 15	723 ± 108
17		Transmission bolt (bracket, engine side)	M16 × 2.0	28.5 ± 3.0	206 ± 21.7
18		Transmission bolt (bracket, T/M side)	M20 × 2.5	57.0 ± 5.0	412 ± 36.2
19		Front axle mounting bolt, nut	M33 × 2.0	225 ± 20	1630 ± 144
20		Rear axle support mounting bolt, nut	M36 × 3.0	308 ± 46.2	2228 ± 334
21		Tire mounting nut	M22 × 1.5	79 ± 2.5	571 ± 18
22	Others	Drive shaft joint mounting bolt, nut	1/2-20UNF	15 ± 2.0	108 ± 14.5
23		Counterweight mounting bolt	M30 × 3.5	199 ± 30	1439 ± 217
24		Operator's seat mounting bolt	M8 × 1.25	3.4 ± 0.8	24.6 ± 5
25		Cab mounting bolt (4EA)	M30 × 3.5	199 ± 30	1440 ± 217
26		Cab mounting nut (4EA)	M16 × 2.0	20.5 ± 4.7	148 ± 40

6. TORQUE CHART

Use following table for unspecified torque.

1) BOLT AND NUT

(1) Coarse thread

Bolt size	8T		10T	
	kg · m	lb · ft	kg · m	lb · ft
M 6 × 1.0	0.85 ~ 1.25	6.15 ~ 9.04	1.14 ~ 1.74	8.2 ~ 12.6
M 8 × 1.25	2.0 ~ 3.0	14.5 ~ 21.7	2.73 ~ 4.12	19.5 ~ 29.8
M10 × 1.5	4.0 ~ 6.0	28.9 ~ 43.4	5.5 ~ 8.3	39.8 ~ 60
M12 × 1.75	7.4 ~ 11.2	53.5 ~ 79.5	9.8 ~ 15.8	71 ~ 114
M14 × 2.0	12.2 ~ 16.6	88.2 ~ 120	16.7 ~ 22.5	121 ~ 167
M16 × 2.0	18.6 ~ 25.2	135 ~ 182	25.2 ~ 34.2	182 ~ 247
M18 × 2.5	25.8 ~ 35.0	187 ~ 253	35.1 ~ 47.5	254 ~ 343
M20 × 2.5	36.2 ~ 49.0	262 ~ 354	49.2 ~ 66.6	356 ~ 482
M22 × 2.5	48.3 ~ 63.3	350 ~ 457	65.8 ~ 98.0	476 ~ 709
M24 × 3.0	62.5 ~ 84.5	452 ~ 611	85.0 ~ 115	615 ~ 832
M30 × 3.0	124 ~ 168	898 ~ 1214	169 ~ 229	1223 ~ 1655
M36 × 4.0	174 ~ 236	1261 ~ 1703	250 ~ 310	1808 ~ 2242

(2) Fine thread

Bolt size	8T		10T	
	kg · m	lb · ft	kg · m	lb · ft
M 8 × 1.0	2.17 ~ 3.37	15.7 ~ 24.3	3.04 ~ 4.44	22.0 ~ 32.0
M10 × 1.25	4.46 ~ 6.66	32.3 ~ 48.2	5.93 ~ 8.93	42.9 ~ 64.6
M12 × 1.25	7.78 ~ 11.58	76.3 ~ 83.7	10.6 ~ 16.0	76.6 ~ 115
M14 × 1.5	13.3 ~ 18.1	96.2 ~ 130	17.9 ~ 24.1	130 ~ 174
M16 × 1.5	19.9 ~ 26.9	144 ~ 194	26.6 ~ 36.0	193 ~ 260
M18 × 1.5	28.6 ~ 43.6	207 ~ 315	38.4 ~ 52.0	278 ~ 376
M20 × 1.5	40.0 ~ 54.0	289 ~ 390	53.4 ~ 72.2	386 ~ 522
M22 × 1.5	52.7 ~ 71.3	381 ~ 515	70.7 ~ 95.7	512 ~ 692
M24 × 2.0	67.9 ~ 91.9	491 ~ 664	90.9 ~ 123	658 ~ 890
M30 × 2.0	137 ~ 185	990 ~ 1338	182 ~ 248	1314 ~ 1795
M36 × 3.0	192 ~ 260	1389 ~ 1879	262 ~ 354	1893 ~ 2561

2) PIPE AND HOSE (FLARE type)

Thread size	Width across flat (mm)	kgf · m	lbf · ft
1/4"	19	4	28.9
3/8"	22	5	36.2
1/2"	27	9.5	68.7
3/4"	36	18	130
1"	41	21	152
1-1/4"	50	35	253

3) PIPE AND HOSE (ORFS type)

Thread size	Width across flat (mm)	kgf · m	lbf · ft
9/16-18	19	4	28.9
11/16-16	22	5	36.2
13/16-16	27	9.5	68.7
1-3/16-12	36	18	130
1-7/16-12	41	21	152
1-11/16-12	50	35	253

4) FITTING

Thread size	Width across flat (mm)	kgf · m	lbf · ft
1/4"	19	4	28.9
3/8"	22	5	36.2
1/2"	27	9.5	68.7
3/4"	36	18	130
1"	41	21	152
1-1/4"	50	35	253

7. RECOMMENDED LUBRICANTS

Use only oils listed below. Do not mix different brand oil.

Please use HYUNDAI genuine oil and grease

Service point	Kind of fluid	Capacity ℓ (U.S. gal)	Ambient temperature °C (°F)						
			-50 (-58)	-30 (-22)	-20 (-4)	-10 (14)	0 (32)	10 (50)	20 (68)
Engine oil pan	Engine oil	34 (9.0)	* ¹ SAE 5W-40						
			SAE 30						
			SAE 10W						
			SAE 10W-30						
			SAE 15W-40						
Transmission	Engine oil	43 (11.4)	SAE 10W-30						
			SAE 15W-40						
Axle	UTTO	Front : 51 (13.5) Rear : 51 (13.5)	*Refer to below list						
Hydraulic tank	Hydraulic oil	Tank: 185 (48.9) System: 295 (77.9)	* ¹ ISO VG 15						
			ISO VG 32						
			ISO VG 46						
			ISO VG 68						
Fuel tank	Diesel fuel	362 (95.6)	* ¹ ASTM D975 NO.1						
			ASTM D975 NO.2						
Fitting (grease nipple)	Grease	As required	* ¹ NLGI NO.1						
			NLGI NO.2						
Radiator (reservoir tank)	Mixture of antifreeze and soft water* ²	46 (12.1)	Ethylene glycol base permanent type (50 : 50)						
			* ¹ Ethylene glycol base permanent type (60 : 40)						

- SAE : Society of Automotive Engineers
- API : American Petroleum Institute
- ISO : International Organization for Standardization
- NLGI : National Lubricating Grease Institute
- ASTM : American Society of Testing and Material
- UTTO : Universal Tractor Transmission Oil

- * Recommended oil list
 - BP TERRAC SUPER TRANSMISSION 10W-30
 - CASTROL AGRI TRANS PLUS 10W-30
 - MOBILFLUID 426
 - SHELL DONAX TD 10W-30
 - TOTAL DYNATRANS MPV

*¹ Cold region : Russia, CIS, Mongolia

*² Soft water : City water or distilled water